
MANUAL.L-TYPE.SEALER

LS Series (Bottom Heating Type)

LS Series Manual L-Type Sealer suitable for small to medium output requirements. Well sealing for center folded PVC or polyolefin shrink films with no smoke or residue. The bottom heating type design Impulse Sealing System delivers consistent jaw pressure and identical seals time after time. It is possible to wrap almost all shapes of product in an fully sealed film wrap. This seal system works well with all shrink films to consistently deliver superior strength seals and reduce maintenance costs.







Features:

• Impulse Sealing

Model Selection: Standard Machine

- Blade Type Heating Element
- Pin wheel hole punch
- Easy Loading Film Dispenser

Stainless Steel Body and Stand

- Adjustable Sealing Time
- Easy Sealing Element and Teflon Tape replacement

= LS-XX

= LS-XX-S

Applications:

- Electronics
- Medical Products
- Frozen Food
- Wholesale Trade
- General Merchandise
- Publishing / Printing

Shrinkable Films: PVC, Polyolefin





Model:	LS-18	LS-24
Seal Size:	(L) 450 mm x (W) 450 mm	(L) 600 mm x (W) 600 mm
Machine Dimensions (mm):	(L) 1200 x (W) 630 x (H) 190	(L) 1350 x (W) 780 x (H) 190
Maximum Product Size (mm):	(L) 400 x (W) 400 x (H) 50	(L) 550 x (W) 550 x (H) 50
Power:	1Φ, 230V, 50Hz, 1.3kW	1Φ, 230V, 50Hz, 1.7kW

SPECIFICATIONS



KITA PACKAGING SDN. BHD.

6537-6538, Jalan Raja Uda, 12300 Butterworth, P.W., Penang, Malaysia. Tel: (604) 331-3487, 331-2201, 332-3908 Fax: (604) 332-3177 **Website:** <u>http://www.kitapackaging.com</u> **Email:** <u>info@kitapackaging.com</u>