

## SINGLE.CHAMBER.VACUUM.PACKAGING.SYSTEM




## VMS-32M

**Features:**

- Splash Proof IP65, Heat Resistance & Soft Touch Control Panel
- Microcomputer Control System,
- Powerful & Large Diameter Vacuum Valve (To Shorten Vacuum Time)
- Aluminum Alloy Sealing Bar (USA Standard)
- Fully Stainless Steel Fabrication
- 20 sets Memory for Programmable Setting
- Single Chamber
- Left and Right Sealing Bar Configuration

**Optional Accessories:**

- Nitrogen Gas Flushing
- Soft Air Sensor
- Pressure Sealing
- Bi-Active Sealing (Top & Bottom Heating)
- Other Chamber Height Available

**Chamber Diagram****Applications:**

Packaging electronic, meat, seafood, agricultural products, pickled foods, vegetarian food, prepared food, powder, spices, medical products and hardware parts.

**Functions:**

- Maintaining food's freshness and flavor; antiseptic, and mold resistant.
- Extend storage period for packed goods.
- Prevents electronic and hardware parts from rusting, oxidization and dampening.
- Suitable for clean room packaging (subjected to vacuum pump exhaust external installation, and type of vacuum pump)

## S P E C I F I C A T I O N S

<b>Chamber Height:</b>	6 1/4"
<b>Machine Dimensions:</b>	(L) 35 1/2" x (W) 26 1/4" x (H) 39 1/2"
<b>Power:</b>	3Φ, 415V, 50Hz, 3hp
<b>Sealing Length:</b>	20 1/2" * 2
<b>Sealing Width:</b>	6mm Double Beam
<b>Pump Capacity:</b>	63 m <sup>3</sup> /H BUSCH Vacuum Pump

**Powered by:**

BUSCH Vacuum Pump, Germany  
NasaVAC LLC, USA

Note: Machine and specifications are subjected to change due to continuous improvement.

**KITA PACKAGING SDN. BHD.**

6537-6538, Jalan Raja Uda, 12300 Butterworth, P.W., Penang, Malaysia.

Tel: (604) 331-3487, 331-2201, 332-3908 Fax: (604) 332-3177

Website: <http://www.kitapackaging.com> Email: [info@kitapackaging.com](mailto:info@kitapackaging.com)